

System Capacity

		KX-TDA600			
		Basic System	2 Shelf System	3 Shelf System	4 Shelf System (Max)
Telephone	Without DXDP*	160	320	480	640
	With DXDP*	240	480	720	960
	Single Line Telephone (SLT)	160	320	480	640
	KX-T7600 series Digital Proprietary Telephone (DPT)	160	320	480	640
	Other DPT	128	256	384	512
	Analogue Proprietary Telephone (APT)	80	160	240	320
	IP-PT (Proprietary Telephone)	160	320	480	640
	Direct Station Select (DSS) Console	64			
Voice Processing System (VPS)	8				
Trunks	Trunk Port	160	320	480	640
	ISDN Trunk	150	300	450	600
	Analogue Trunk	160	320	480	640
	IP-Gateway	160	320	480	640
Wireless	Portable Station (PS)	Without Memory Expansion Card	256		
		With Memory Expansion Card	512		
	Cell Station (CS)	32	64	96	128
Doorphone Port		16	32	48	64
PC Console		8	8	8	8
PC Phone		128	128	128	128

*DXDP: Digital eXtra Device Port

Option List for TDA600

	Model	Description	
Cabinet	KX-TDA600 (Proprietary)	Basic Shelf (Main Unit)	
	KX-TDA620 (Proprietary)	Expansion Shelf Bus Slave Connection Circuit added initially (BUS S)	
Power Supply	KX-TDA0103	Large Power Supply Unit (L-PSU)	
	KX-TDA0104	Medium Power Supply Unit (M-PSU)	
EMPR	Daughter cards for EMPR card only	KX-TDA6105	Memory Expansion Card (EMEC)
		KX-TDA0196	Remote Card (RMT)
Inter Connection	KX-TDA6110	Shelf Connection Card for Basic Shelf (BUS M)	
	KX-TDA6111	Additional Card for connecting Expansion Shelf 2 and 3 (BUS ME) Mounted onto Bus M Card	
Extension Cards	KX-TDA0170	8-Port Digital Hybrid Extension Card (DHLC8)	
	KX-TDA0171	8-Port Digital Extension Card (DLC8)	
	KX-TDA0172	16-Port Digital Extension Card (DLC16)	
	KX-TDA0173	8-Port Single Line Telephone Card (SLC8)	
	Daughter card for SLC8 card only	KX-TDA0168	8-Port Analogue Extension Caller ID card (EXT-CID8)
	KX-TDA6174	16-Port Single Line Telephone Card (ESLC16)	
	KX-TDA6175	16-Port Single Line Telephone Card with Message Lamp (EMSLC16)	
KX-TDA0470	16-Port IP PT Extension Card (IP-EXT16)		
Trunk Cards	KX-TDA6181	16-Port Analogue Trunk Card (ELCOT16)	
	Daughter cards for LCOT cards only	KX-TDA0189	8-Port Caller ID / Pay Tone Card (CID / PAY8)
		KX-TDA0193	8-Port Caller ID Card (CID8)
	KX-TDA0182	8-port Direct Dialling In (DID) Card (DID8)	
	KX-TDA0184	8-Port E&M Trunk Card (E&M8)	
	KX-TDA0188	E-1 Trunk Card (E1)	
	KX-TDA0284	4-Port Basic Rate Interface (BRI) Card (BRI4)	
	KX-TDA0288	8-Port Basic Rate Interface (BRI) Card (BRI8)	
	KX-TDA0290	Primary Rate Interface (PRI) Card (PRI 30)	
	KX-TDA0484	4-Channel VoIP Gateway Card (IP-GW4E)	
	KX-TDA0490	16-Channel VoIP Gateway Card (IP-GW16)	
Dect Options	KX-TDA0141	2-Channel Cell Station Unit Using a DHLC / DLC Card for DECT Portable Station	
	KX-TDA0142	4-Channel Cell Station Unit Using a CSIF Card for DECT Portable Station	
	KX-TDA0143	4 Cell Station Interface Card (CSIF4) for TDA0142	
	KX-TDA0144	8 Cell Station Interface Card (CSIF8) for TDA0142	
	KX-A272	2-Channel DECT Cell Station Repeater	
Option Cards	KX-TDA0190	Optional 3-Slot Base Card (OPB3)	
	KX-TDA0410	CTI Link Card (TAPI / CSTA, 10Base-T)	
	KX-TDA6166	16-Channel Echo Canceller Card (ECHO16)	
	Daughter cards for OPB3 card only	KX-TDA0161	4-Port Doorphone Card (for KX-T30865) (DHP4)
		KX-TDA0162	2-Port Doorphone Card (for German Type) (DPH2)
KX-TDA0164		4-Port External sensor Card (EIO4)	
KX-TDA0191		4-Channel Message Card (MSG4)	
Other	KX-TDA6920	SD Card containing Enhanced Feature Upgrades	
	KX-TDA6201	Mounting Kit - Contains 4 x Wall Mounting Plates, 4 x Feet, and Screws	

Specifications

KX-TDA600
Power Voltage: AC100V ~ 240V
External Battery: +36V (+12V x 3), Built-in interface
Memory Back-up Duration: 7 years
Dialling: Extension - DP (10pps, 20pps), DTMF CO - DP (10pps, 20pps), DTMF
Mode Conversion: DP-DTMF, DTMF-DP
Connectors: CO Line - Amphenol Connector Station - Amphenol Connector Paging Output - 2 conductor jack External Voice Output - 2 conductor jack
Ring Frequency: 20 / 25 Hz (Selectable)
Central Office Loop Limit: 1600 ohms max.
Operating Environment: Temperature - 0 - 40°C (32 - 104°F) Humidity - 10 - 90%
MOH (Music on Hold): 2 ports MOH # 1: External Music Source MOH # 2: Internal Music / External Music Source (Level control: -6dB ~ +6dB per 3dB)
Internal Paging: Level control: -6dB ~ +6dB per 3dB
External Paging: 2 ports (Level control: -15dB ~ +15dB per 3dB)
Serial Interface Port: USB: 1port RS-232C; 1port (115.2kbps)
Structure: Free Slot style Can be accommodated into 19" Rack

System Feature Capacity

		KX-TDA600
System	Tenant	8
	Class of Service	64
	Trunk Group	96
	User Group	96
	Paging Group	96
	Call Pickup Group	96
	Incoming Call Distribution (ICD) Group	128 groups, 128 extensions per group
	Portable station (PS) Ring Group	32
	Voice Mail (DPT) Group	8
	Voice Mail (DTMF) Group	8
	Queueing Time Table	64
	Extension Hunting Group	128 groups (16 extensions per group)
	Absent Message (System / Extension)	8 message x 16 characters per system 1 message x 16 characters per extension
	Message Waiting	1672 (1032: PT+SLT) + (640: ICDG+PS)
	Number of the characters of Name	20
	Extension Number Digits	5 digits
	Call Park Zone	100
	Conference	3x10 - 8x4 per shelf
	Special Carrier Code	16 digits, 100 entries
	Verified Code	4 digits x 1000 entries
	Verified Code Personal Identification Number (PIN)	10 digits, 1000 entries
	Host PBX Access Code	10 digits (10 entries / trunk group)
	DDI / DID Table	32 digits (1000 entries)
Station Message Detailed Recording (SMDR) Call Storage	1000 calls w/o EMEC card 4000 calls w EMEC card	
Toll Restriction / Barring	Toll Restriction / Barring Level	7
	Toll Restriction / Barring Denied Code	16 digits, 100 entries per level
	Toll Restriction / Barring Exception Code	16 digits, 100 entries per level
Networking	TIE Routing Table	32 entries
	Leading Number	3 digits
	PBX Code	7 digits

		KX-TDA600
Automatic Route Selection (ARS)	Routing Plan Table	48 entries
	Leading Number Table	16 digits, 1000 entries
	Leading Number Exception Table	16 digits, 200 entries
	ARS Carrier	48
	Itemised Billing Code	10 digits
	Authorisation Code	10 digits
Dialling	Emergency Call	32 digits, 10 entries
	Quick Dialling	4 digits, 80 entries w/o EMEC card (4 digits, 80 entries) + (8 digits, 1000 entries) w EMEC card
	System Speed Dialling	32 digits, 1000 entries per system w/o EMEC card 32 digits, 1000 entries per Tenant w EMEC card Max: 8 Tenants
	Personal Speed Dialling	32 digits, 10 entries per extension w/o EMEC 32 digits, 100 entries per extension w EMEC
	One-Touch Dialling	32 digits
	Hot Line	32 digits
	Key Pad Protocol Dial (ISDN Service Access)	32 digits
	Redial	32 digits
Password	System Password for Administrator	4-10 digits
	System Password for User	4-10 digits
	Manager Password	4-10 digits
	Extension Personal Identification Number (PIN)	0-10 digits / extension
Voice Mail	Max Number of VPS Systems	8
	Max Number of VPS Channels	8 x 24ch
Call Log	Outgoing Call Log	10 logs per extension 5 x 1152 logs per system
	Incoming Call Log	100 logs per extension 10 x 1280 logs per system

Features List

System Features

- Automatic ISDN Setting (BRI)
- Automatic Route Selection (ARS) / Least Cost Routing (LCR)
- Background Music (BGM)
- Budget Management
- Busy on Busy
- Call Park with Indication
- Call Pickup Group
- Call distribution by Caller ID
- Class of Service (COS)
- CTI (CSTA, TAPI)
- Data Line Security
- Delayed Ringing
- Direct In Lines (DIL)
- Direct Inward Dialling (DID)
- Direct Inward System Access (DISA)
- Door-Phone / Door Opener
- Echo Cancellation
- Extension Lock
- Emergency Call
- Existing APT/ DPT Compatibility
- External BGM
- Flexible Numbering Plan (4-digits)
- Floating Extension
- Greeting Message
- Host PBX Access Code
- Hunting Group
- Hurry-Up Transfer
- Incoming Group (Hunting Group)
- Intercept Routing - Busy / DND
- Intercept Routing - No Answer
- Intercept to Trunk
- Line Monitor (CO)
- Main Processing (MPR), Card / CS software download
- Manager Functions
- Multiple Language Support
- Online Diagnostics
- Operator Functions
- PC Console / PC Phone
- PC Programming
- Paging Group
- Quick Setup
- Remote Alarm Notification
- Remote Extension Status Control through DISA
- Remote Extension Lock
- Ring Group
- Special Carrier Access
- Station Message Detail Recording (SMDR)
- SMDR 24 Hour and 12 Hour Time Format
- SMDR Caller ID Printing
- System Memory Expansion
- Tenant Service
- Timed Reminder
- Time Service (Day / Night / Lunch / Break)
- Toll Restriction
- Trunk Group
- Uniform Call Distribution (UCD)
- User Group
- VIP-Call
- Visual Caller ID

<Voice Mail (VM) Features>

- Automatic Configuration - Quick Setup
- Call Forwarding to VM
- Caller's Identification Notification to VM
- Intercept Routing to VM
- Telephone Display, Menu driven VM operation
- Live Call Screening (LCS)
- Remote PBX Data Control by VM
- VM Data Control by PBX
- VM (Digital / DTMF) Integration
- VM Group
- VM Mail Transfer
- VM Message Number display on DPT LCD

Extension Features

- 4-Party Conference with Broadcasting up to 32-Party
- Absent Message
- Account Code Entry (Forced)
- Automatic Redial
- Boss - Secretary
- Broadcasting
- Caller ID to Single Line Telephone
- Call Forwarding (All Calls, Busy, Busy / No Answer, No Answer, Follow Me, From Incoming Group)
- Call Hold
- Call Pickup (Directed, Group, DSS, Deny)
- Call Transfer (Screened, Unscreened, One-Touch Transfer, Transfer Recall)
- Conference (3-Party Conference, Multi Party Conference, Unattended Conference)
- Dial Type Selection
- Digital eXtra Device Port (DXDP) (2DPTs in One Extension Port)
- Direct One-Touch Answering
- Do Not Disturb (DND)
- DSS Console
- Executive Busy Override
- Extension Directory
- Extension-to-Trunk Call Duration Time
- External Feature Access
- Flexible Buttons
- Digital Duplex SP-phone
- Hands-free Operation
- Handset / Headset Selection
- Large Telephone Display Features with Back-lit
- LED control for CTI
- Log-In / Log-Out
- Message Waiting
- Multi-Lingual Display
- Multiple Hop Call Forwarding (4 steps)
- Music on Hold
- Off-Hook Call Announcement (OHCA)
- Off-Hook Monitor
- One-Touch Dialling
- Paging (Deny, Paging Transfer)
- Paralleled Telephone (APT / DPT+SLT, DPT / SLT+PS)
- Redial, Last Number
- Remote Station Control
- Special Carrier Access
- Speed Dialling - Personal / System
- Time and Date Display

- Tone-Pulse Conversion
- Trunk Answer from Any Station (TAFAS)
- Walking Class Of Service (COS)
- Whisper OHCA (Off-Hook Call Announcement)
- Wrap-Up
- eXtra Device Port (XDP)

<DECT Features>

- Automatic Handover
- DECT CS on Digital Extension Port
- Headset Compatibility
- Incoming & Outgoing Call Log
- Telephone Display control via CTI*
- Wireless XDP Parallel Mode
- Vibrator Ring (KX-TCA255 only)

ISDN Service Features

- Advice Of Charge (AOC)
- Calling Line Identification Restriction (CLIR)
- Calling Line Identification Presentation (CLIP)
- Completion of Calls to Busy Subscriber (CCBS)
- Connected Line Identification Presentation (COLP)
- Connected Line Identification Restriction (COLR)
- Direct Dialling Inward (DDI)
- ISDN 3 Party Conference (3PTY)
- ISDN Call Forward (CFU / CFNR / CFB)
- ISDN Call Transfer (CT)
- ISDN Extension
- Malicious Call Identification (MCID)
- Multiple Subscriber Numbers (MSN)

Networking Features

- Alternated Routing
- ARS with VoIP
- Network Busy Lamp Field (BLF)*
- Caller ID to SLT (Public Call through Private Network)
- Call Log (Public Call through Private Network)
- Network Closed Numbering
- DISA Call to the Network
- Private Network to Public Network
- Public Network to Private Network
- QSSIG Connection
- Speed Dial Name (Public Call through Private Network)
- Tandem Connection
- Transfer to Network PBX
- Virtual Private Network (VPN)
- VoIP Network (Built-in IP-GW)

*Optional software required
 DPT: Digital Proprietary Telephone
 APT: Analogue Proprietary Telephone
 SLT: Single Line Telephone
 PS: Portable Station